

Application No. 10/089,593
Filed: August 6, 2002
TC Art Unit: 1734
Confirmation No.: 2476

AMENDMENTS TO THE CLAIMS

1/- (currently amended) Prefabricated material in the form of a one or more thin flexible polymer sheet-sheets for making hot-tensioned structures in respective frames, each hot-tensioned structure being encompassed by one of the respective frames to form a false ceiling or a false wall~~such as false ceilings,~~ ~~in particular,~~ the material being characterized in that it carries direct printing of designs of shapes and dimensions that are predetermined once the material is hot-tensioned.

2/- (currently amended) A~~The~~ material according to claim 1, characterized in that it is selected from the group comprising thermoplastic polymers ~~such as~~including plasticized polyvinyl chloride and polymers derived therefrom as superchlorinated vinyl chloride, polyvinylidene chloride, and copolymers of vinyl chloride and polyvinylidene chloride.

3/- (currently amended) A~~The~~ material according to claim 1, characterized in that it is a multilayer material.

4/- (currently amended) A~~The~~ material according to claim 1, characterized in that it is mono- or bi-oriented.

Application No. 10/089,593
Filed: August 6, 2002
TC Art Unit: 1734
Confirmation No.: 2476

5/ (withdrawn) A method of making a hot-tensioned false ceiling, by hot-tensioning a material of the kind presented in claim 1, in a false ceiling obtained by assembling rails, the method being characterized in that it comprises:

- a step of selecting designs to be printed on the material, said designs being mono- or polychromatic and being capable of being modified in shape, color, proportions, and dispositions, said designs being digitized and recorded in a computer memory of a system for controlling a printing machine; and

- a step of printing the selected design on the flexible polymer material in sheet form.

6/ (withdrawn) A method according to claim 5, characterized in that it includes a step of printing a final design as selected by the user on paper.

7/ (withdrawn) A method according to claim 6, characterized in that the printing is performed by means of a silkscreen printing machine.

Application No. 10/089,593
Filed: August 6, 2002
TC Art Unit: 1734
Confirmation No.: 2476

8/ (withdrawn) A method according to claim 6, characterized in that the printing is performed by means of a digital ink jet machine.

9/ (withdrawn) A method according to claim 6, characterized in that the printing is performed on a plurality of bonded-together strips of material, and in particular is performed over the zones in which the strips are bonded together edge to edge.

10/ (withdrawn) A method according to claim 6, characterized in that the printing is performed on each strip of material with the strips being assembled together by bonding performed after the printing.

11/ (withdrawn) A method according to claim 10, characterized in that it includes a step of predeforming the design to be printed on the flexible polymer material, the predeformation taking account of differential lengthening of the printed material during hot-tensioning, said predeformation substantially compensating for distortion in the design caused by the material being hot-tensioned and thus ensuring that a properly proportioned design is obtained on the tensioned printed material.

-5-

WEINGARTEN, SCHURIN,
GAGNEBIN & LESOVICI LLP
TEL. (617) 542-2290
FAX. (617) 451-0313

Application No. 10/089,593

Filed: August 6, 2002

TC Art Unit: 1734

Confirmation No.: 2476

12/ (withdrawn) A false ceiling obtained by implementing the method presented in claim 5, characterized in that a catch member is defined in the frame of the false ceiling, the catch member being capable of receiving a margin member disposed along the periphery of the sheet of flexible polymer material that is hot-tensioned in said frame.

13/ (withdrawn) 'A false ceiling according to claim 12, characterized in that the margin member is bonded close to the peripheral edge of the tensioned sheet, said bonding being hidden from view by portions of the rails of the frame.

14/ (currently amended) A The material according to claim 2, characterized in that it is a multilayer material.

15/ (currently amended) A The material according to claim 2, characterized in that it is mono- or bi-oriented.

16/ (currently amended) A The material according to claim 3, characterized in that it is mono- or bi-oriented.

-6-

WEINGARTEN, SCHURGIN,
GAGNESIN & LEBOVICI LLP
TEL. (617) 542-2290
FAX. (617) 451-0313

Application No. 10/089,593
Filed: August 6, 2002
TC Art Unit: 1734
Confirmation No.: 2476

17/ (withdrawn) A method of making a hot-tensioned false ceiling, by hot-tensioning a material of the kind presented in claim 2, in a false ceiling obtained by assembling rails, the method being characterized in that it comprises:

- a step of selecting designs to be printed on the material, said designs being mono- or polychromatic and being capable of being modified in shape, color, proportions, and dispositions, said designs being digitized and recorded in a computer memory of a system for controlling a printing machine; and

- a step of printing the selected design on the flexible polymer material in sheet form.

18/ (withdrawn) A method of making a hot-tensioned false ceiling, by hot-tensioning a material of the kind presented in claim 3, in a false ceiling obtained by assembling rails, the method being characterized in that it comprises:

- a step of selecting designs to be printed on the material, said designs being mono- or polychromatic and being capable of being modified in shape, color, proportions, and dispositions, said designs being digitized and recorded in a computer memory of a system for controlling a printing machine; and

Application No. 10/089,593
Filed: August 6, 2002
TC Art Unit: 1734
Confirmation No.: 2476

- a step of printing the selected design on the flexible polymer material in sheet form.

19/ (withdrawn) A method of making a hot-tensioned false ceiling, by hot-tensioning a material of the kind presented in claim 4, in a false ceiling obtained by assembling rails, the method being characterized in that it comprises:

- a step of selecting designs to be printed on the material, said designs being mono- or polychromatic and being capable of being modified in shape, color, proportions, and dispositions, said designs being digitized and recorded in a computer memory of a system for controlling a printing machine; and

- a step of printing the selected design on the flexible polymer material in sheet form.

20/ (withdrawn) A method of making a hot-tensioned false ceiling, by hot-tensioning a material of the kind presented in claim 19, in a false ceiling obtained by assembling rails, the method being characterized in that it comprises:

- a step of selecting designs to be printed on the material, said designs being mono- or polychromatic and being capable of being modified in shape, color, proportions, and dispositions,

Application No. 10/089,593
Filed: August 6, 2002
TC Art Unit: 1734
Confirmation No.: 2476

said designs being digitized and recorded in a computer memory of a system for controlling a printing machine;

- a step of printing the selected design on the flexible polymer material in sheet form; and

- a step of printing a final design as selected by the user on paper by means of one of a silkscreen printing machine or a digital ink jet machine.

21/ (withdrawn) A method according to claim 20, characterized in that the printing is performed on a plurality of bonded-together strips of material, and in particular is performed over the zones in which the strips are bonded together edge to edge.

22/ (withdrawn) A method according to claim 20, characterized in that:

the printing is performed on each strip of material with the strips being assembled together by bonding performed after the printing;

it includes a step of predeforming the design to be printed on the flexible polymer material, the predeformation taking account of differential lengthening of the printed material during hot-tensioning, said predeformation substantially compensating for

Application No. 10/089,593
Filed: August 6, 2002
TC Art Unit: 1734
Confirmation No.: 2476

distortion in the design caused by the material being hot-tensioned and thus ensuring that a properly proportioned design is obtained on the tensioned printed material.

23/ (withdrawn) A false ceiling obtained by implementing the method presented in claim 20, characterized in that:

a catch member is defined in the frame of the false ceiling, the catch member being capable of receiving a margin member disposed along the periphery of the sheet of flexible polymer material that is hot-tensioned in said frame;

the margin member is bonded close to the peripheral edge of the tensioned sheet, said bonding being hidden from view by portions of the rails of the frame.

24/ (withdrawn) A false ceiling obtained by implementing the method presented in claim 21, characterized in that:

a catch member is defined in the frame of the false ceiling, the catch member being capable of receiving a margin member disposed along the periphery of the sheet of flexible polymer material that is hot-tensioned in said frame;

Application No. 10/089,593
Filed: August 6, 2002
TC Art Unit: 1734
Confirmation No.: 2476

the margin member is bonded close to the peripheral edge of the tensioned sheet, said bonding being hidden from view by portions of the rails of the frame.

25/ (withdrawn) A false ceiling obtained by implementing the method presented in claim 22, characterized in that:

a catch member is defined in the frame of the false ceiling, the catch member being capable of receiving a margin member disposed along the periphery of the sheet of flexible polymer material that is hot-tensioned in said frame;

the margin member is bonded close to the peripheral edge of the tensioned sheet, said bonding being hidden from view by portions of the rails of the frame.

-11-

WEINGARTEN, SCHURGIN,
GAGNEBIN & LEBOVICI LLP
TEL. (617) 542-2290
FAX. (617) 451-0313